








Water Level Meter	Tape/Cable Type & Length	Probe Features & Materials	Measurement Indicators	Frame & Reel Specifications	Advantages
<b>Model 101 P7</b> 	<ul style="list-style-type: none"> <li>Flat (dog bone) PVDF</li> <li>Laser markings: 1/100 ft or mm - certified traceable to National Standards</li> <li>19 strands of stainless steel in each conductor, 6 of those are copper coated</li> <li>3/8" (10 mm) width</li> <li><b>Lengths</b> to 5000 ft (1500 m)</li> </ul>	<ul style="list-style-type: none"> <li>P7 submersible 316 stainless steel</li> <li>Probe with Delrin® tape seal plug</li> <li>5/8" (16 mm) diameter, 5.38" (137 mm) length</li> <li>128 grams (4.5 ounces)</li> </ul>	<ul style="list-style-type: none"> <li>LED light</li> <li>Buzzer</li> <li>On/Off sensitivity switch</li> <li>Battery test button</li> </ul>	<ul style="list-style-type: none"> <li>Plastic faceplate &amp; backplate (small reels)</li> <li>Metal faceplate &amp; backplate (medium &amp; large reels)</li> <li>Plastic hub</li> <li>Battery drawer</li> <li>Free-standing frame</li> <li>Brake &amp; probe holder</li> <li>Tape Guide</li> </ul>	<ul style="list-style-type: none"> <li>Probe submersible to 1000 ft (300 m)</li> <li>Probe is simple to replace</li> <li>Tape is extremely durable, high in tensile strength and electrical efficiency</li> <li>Sensor at tip of probe, almost zero displacement</li> </ul>
<b>Model 101 P2</b> 	<ul style="list-style-type: none"> <li>Flat (dog bone) polyethylene</li> <li>Heat embossed markings: 1/100 ft or each mm</li> <li>Foot and meter markings in red</li> <li>7 strands of stainless steel in each conductor</li> <li>3/8" (10 mm) width</li> <li><b>Lengths</b> to 1000 ft (300 m)</li> </ul>	<ul style="list-style-type: none"> <li>P2 316 stainless steel</li> <li>Probe with Neoprene heat shrink seal</li> <li>0.55" (14 mm) diameter, 7.5" (190 mm) length</li> <li>200 grams (7 ounces)</li> </ul>	<ul style="list-style-type: none"> <li>LED light</li> <li>Buzzer</li> <li>On/Off sensitivity switch</li> <li>Battery test button</li> </ul>	<ul style="list-style-type: none"> <li>Plastic faceplate &amp; backplate (small reels)</li> <li>Metal faceplate &amp; backplate (medium reels)</li> <li>Plastic hub</li> <li>Battery drawer</li> <li>Free-standing frame</li> <li>Brake &amp; probe holder</li> <li>Tape Guide</li> </ul>	<ul style="list-style-type: none"> <li>Easy to repair probe</li> <li>Shielded probe</li> <li>Tape is very easy to splice</li> <li>Tape is very flexible</li> </ul>
<b>Model 101B</b> 	<ul style="list-style-type: none"> <li>Flat (dog bone) polyethylene tape with heat embossed markings each cm</li> <li>7 strands of stainless steel in each conductor</li> <li>3/8" (10 mm) width</li> <li>30 m, 60 m, 100 m <b>Lengths</b></li> </ul>	<ul style="list-style-type: none"> <li>P1 316 stainless steel</li> <li>Probe</li> <li>5/8" (16 mm) effective diameter, 4" (102 mm) length</li> <li>100 grams (3.53 ounces)</li> </ul>	<ul style="list-style-type: none"> <li>LED light</li> <li>Buzzer</li> </ul>	<ul style="list-style-type: none"> <li>Plastic faceplate &amp; backplate</li> <li>Plastic hub</li> <li>Handle</li> <li>Brake</li> <li>Probe holder (metal clamp) on front of faceplate</li> </ul>	<ul style="list-style-type: none"> <li>Low cost</li> <li>Easy to repair</li> </ul>
<b>Model 102 P10</b> 	<ul style="list-style-type: none"> <li>Cable with laser markings each 1/100 ft or each mm</li> <li>Copper outer conductor, stainless steel central conductor, heavy-duty polyethylene jacket</li> <li>0.120" (3.05 mm) diameter</li> <li><b>Lengths</b> to 1000 ft (300 m)</li> </ul>	<ul style="list-style-type: none"> <li>P10 316 stainless steel</li> <li>Probe with 10 stainless steel weights</li> <li>3/8" (9.5 mm) diameter, 2.75" (70 mm) length</li> <li>174 grams (6.14 ounces) (with weights)</li> </ul>	<ul style="list-style-type: none"> <li>LED light</li> <li>Buzzer</li> <li>On/Off sensitivity switch</li> <li>Battery test button</li> </ul>	<ul style="list-style-type: none"> <li>Plastic faceplate &amp; backplate</li> <li>Plastic hub</li> <li>Battery drawer</li> <li>Free-standing frame</li> <li>Brake &amp; probe holder</li> <li>Tape Guide</li> </ul>	<ul style="list-style-type: none"> <li>Ability to fit narrow diameters and snake around down-well obstructions or pumps</li> <li>Lower cost</li> </ul>
<b>Model 102 P4</b> 	<ul style="list-style-type: none"> <li>Cable with laser markings each 1/100 ft or each mm</li> <li>Copper outer conductor, stainless steel central conductor, heavy-duty polyethylene jacket</li> <li>0.120" (3.05 mm) diameter</li> <li><b>Lengths</b> to 300 ft (100 m)</li> </ul>	<ul style="list-style-type: none"> <li>P4 316 stainless steel</li> <li>Probe with no weights</li> <li>0.157" (4 mm) diameter, 1.5" (38 mm) length</li> <li>10 grams (0.35 ounces)</li> </ul>	<ul style="list-style-type: none"> <li>LED light</li> <li>Buzzer</li> <li>On/Off sensitivity switch</li> <li>Battery test button</li> </ul>	<ul style="list-style-type: none"> <li>Plastic faceplate &amp; backplate</li> <li>Plastic hub</li> <li>Battery drawer</li> <li>Free-standing frame</li> <li>Brake &amp; probe holder</li> <li>Tape Guide</li> </ul>	<ul style="list-style-type: none"> <li>Ability to fit narrow diameters, including the channels of a Solinst CMT Multilevel System or open tubes of a Waterloo System</li> <li>Lower cost</li> </ul>
<b>Model 102M P10</b> 	<ul style="list-style-type: none"> <li>Cable with laser markings each 1/100 ft or each mm</li> <li>Copper outer conductor, stainless steel central conductor, heavy-duty polyethylene jacket</li> <li>0.120" (3.05 mm) diameter</li> <li>80 ft or 25 m <b>Lengths</b></li> </ul>	<ul style="list-style-type: none"> <li>P10 316 stainless steel</li> <li>Probe with 10 stainless steel weights</li> <li>3/8" (9.5 mm) diameter, 2.75" (70 mm) length</li> <li>174 grams (6.14 ounces) (with weights)</li> </ul>	<ul style="list-style-type: none"> <li>LED light</li> <li>Buzzer</li> <li>On/Off sensitivity switch</li> <li>Battery test button</li> </ul>	<ul style="list-style-type: none"> <li>Plastic faceplate &amp; backplate</li> <li>Plastic hub</li> <li>Handle</li> <li>Brake</li> <li>Probe holder</li> </ul>	<ul style="list-style-type: none"> <li>Small compact reel makes it easy to transport</li> <li>Ability to fit narrow diameters and snake around down-well obstructions or pumps</li> <li>Lower cost</li> </ul>
<b>Model 102M P4</b> 	<ul style="list-style-type: none"> <li>Cable with laser markings each 1/100 ft or each mm</li> <li>Copper outer conductor, stainless steel central conductor, heavy-duty polyethylene jacket</li> <li>0.120" (3.05 mm) diameter</li> <li>80 ft or 25 m <b>Lengths</b></li> </ul>	<ul style="list-style-type: none"> <li>P4 316 stainless steel</li> <li>Probe with no weights</li> <li>0.157" (4 mm) diameter, 1.5" (38 mm) length</li> <li>10 grams (0.35 ounces)</li> </ul>	<ul style="list-style-type: none"> <li>LED light</li> <li>Buzzer</li> <li>On/Off sensitivity switch</li> <li>Battery test button</li> </ul>	<ul style="list-style-type: none"> <li>Plastic faceplate &amp; backplate</li> <li>Plastic hub</li> <li>Handle</li> <li>Brake</li> <li>Probe holder</li> </ul>	<ul style="list-style-type: none"> <li>Small compact reel makes it easy to transport</li> <li>Ability to fit narrow diameters, including the channels of a Solinst CMT Multilevel System or open tubes of a Waterloo System</li> <li>Lower cost</li> </ul>